
SECTION 1 : IDENTIFICATION

PRODUCT NAME: Universal Top Coat
Product Use: Nail Gel
91311-4020148
Manufacturer's Name : Star Nail International Chemical Family :
Address : 29120 Avenue Paine Proprietary Mix
City, State, Zip : Valencia, CA 91355 CAS# N/A

24 HR. EMERGENCY TELEPHONE: CHEMTEL 1-813-248-0573

SECTION 2: HAZARDOUS IDENTIFICATION

EMERGENCY OVERVIEW

This information may be based on findings from related or similar materials.

- May be slightly toxic.
- May cause moderate skin injury (reddening & swelling).
- May cause eye irritation.

Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry No specific information is available for this product. Although, this product opposes only slight irritation concern with all routes of entry.

Eye No specific information available. Contains materials that are essentially nonirritating, but contact may cause slight transient irritation.

Skin No specific information available. Contains materials that may cause moderate skin injury (reddening and swelling) and/or sensitization. Prolonged contact may cause blister formation (burns). Since irritation may not occur immediately, contact can go unnoticed.

Ingestion No specific information available. Contains materials that may be practically nontoxic.

Inhalation No specific information available. Low volatility makes vapor inhalation unlikely.

Sub-Chronic Effects No specific information available. Limited tests showed no evidence of teratogenicity in animals. A lifetime skin painting study with mice showed no evidence of carcinogenicity.

NOTE: Refer to Section 11, Toxicological Information for Details

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

SECTION 3 : COMPOSITION/ INFORMATION on INGREDIENTS

Chemical Identify	CAS#	EINECS#	INCI Name	Exposure OSHA TWA/STEL	Limits ACGIH TWA/STEL	Carcinogen IARC/NTP/OSHA	%
Polyurethane Acrylate Oligomer	Exempt	N/E	Di-Hema Trimethylhexyl Dicarbamate*	N/E	N/E	NOT LISTED	50-60
2-Hydroxyethyl Methacrylate	868-77-9	212-782-2	HEMA	N/E	N/E	NOT LISTED	15-20
Hydroxypropyl Methacrylate	27813-02-1	248-666-3	Hydroxypropyl methacrylate	N/E	N/E	NOT LISTED	15-20
Hydroxycyclohexyl phenyl ketone	947-19-3	213-426-9	Hydroxycyclohexyl phenyl ketone	N/E	N/E	NOT LISTED	0-1
D&C Violet #2	81-48-1	201-353-5	Violet 2/CI60725	N/E	N/E	NOT LISTED	0-1

N/E - None Established N/R - Not Reviewed N/DA - No Data Available N/A - Not Applicable * See section 16 Risk & Safety Phrase

SECTION 4 : FIRST AID MEASURES

First Aid for Eye:	Flush with plenty of water for 15 minutes and retract eyelids often. Seek medical attention immediately.
First Aid for Skin:	Remove contaminated clothing and wash contact area with soap and water for 15 minutes.
First Aid for Inhalation: person	In case of exposure to a high concentration of vapor or mist, remove to fresh air. If breathing has stopped, administer artificial respiration and seek medical attention.

SECTION 5 : FIRE FIGHTING MEASURES

FLASH POINT (F/C)	FLAMMABLE LIMIT (vol %)	AUTO-IGNITION TEMPATURE (vol %)
>212F/100C Setflash	No Data	No Data

METHOD:

Extinguishing Media	Use carbon dioxide or dry chemical for small fires; aqueous foam or water for large fires.
Fire Fighting Instructions:	Remove all ignition sources. Wear self-contained breathing apparatus and complete personal protective equipment when entering confined areas where potential for exposure to vapors or products of combustion exists.
Unusual Hazards:	High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in explosions and the violent rupture of storage vessels or containers. Avoid the use of a stream of water to control fires since frothing can occur.

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

Spill or Release Spontaneous polymerization can occur. Eliminate ignition sources. Use eye and skin protection. Place leaking containers in a well ventilated area. Dike and recover large spills. Soak up small spills with inert solids (such as vermiculite, clay) and sweep/shovel into disposal container. Wash spill area with strong detergent and water solution; rinse with water, but minimize water use during clean-up. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. Dispose and report per regulatory requirements if necessary. Please prevent washings from entering waterways.

SECTION 7 : HANDLING & STORAGE

Handling: Avoid contact with skin and eyes. Avoid breathing vapor. Keep container closed when not in use. Avoid prolonged exposure to light. Remove all contaminated clothing, shoes, belts and other leather goods immediately. Incinerate leather goods (including shoes). Wash contaminated clothing thoroughly before reuse. Wash skin thoroughly with soap and water after handling. Solvents should not be used to clean skin because of increased penetration potential. Most acrylic monomers have low viscosities, thus only needing room temperature conditions to facilitate proper pouring techniques. However, viscous type gels such as these may require heating to facilitate proper pouring techniques. To ensure that this happens, product may be heated to 60°C/140°F for not more than 24 hours. Do NOT use localized heat sources such as band heaters to heat/melt product. Do NOT use steam. Hot boxes or hot rooms are recommended for heating/melting material. The hot box and/or room should only be set to a maximum temperature of 60°C/140°F. Do not overheat, this may compromise product effectiveness and should be avoided. Refrain from multiple reheatings of product, this will also diminishing the quality of the product.

Storage: Product is extremely light sensitive. If exposed to natural light or UV light, material will cure very quickly. Store in a cool, dry place, away from heat and all types of light. Store at temperatures below 100°F/38°C but above the product's freezing point. If no freezing point is given, keep above 32°F/0°C at all times.

Explosion Hazard: High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in explosions and the violent rupture of storage vessels or containers.

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

SECTION 8 : EXPOSURE CONTROLS/ PERSONAL PROTECTION

Engineering Controls: Local exhaust recommended to control exposure which may result from operations generating aerosols and hot operations generating vapors.

Personal Protective Equipment:

General To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a Hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product . Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than PVC.

Eye/ Face Protection Wear chemical splash goggles.

Skin Protection Wear impervious gloves (Neoprene).

Respiratory Protection A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by nuisance level organic vapor dust masks can be used, however the use of the respirator is limited. Follow OSHA respirator regulations found in 29 CFR 1910.134 or European Stan

SECTION 9 : PHYSICAL & CHEMICAL PROPERTIES

Appearance	Odor & Odor Threshold	PH	Specific Gravity	Viscosity	% Volatile		
Clear to slight violet, viscous liquid	characteristic acrylate odor	NA	(H2O=1) : 1.15	N/DA By Volume :	< 0.5		
Boiling Point/ Freezing Point	Decomposition Temperature	Octanol/Water Partitioning Coefficient	Vapor Pressure:	Vapor Density	Evaporation Rate	Ignition In Water (20°C)	Solubility
N/A	N/A	Log Po/w N/A	(mm Hg)@20 C : < 0.01	No Data	No Data	No Data	Insoluble
Flash Point (°F/°C)	Flammable Limit (vol%)	Auto-ignition Temperature (vol%)					
> 212°F/100°C Setflash	No Data	No Data					

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

 SECTION 10: STABILITY & REACTIVITY

Stability

Normally Stable

Hazardous Decomposition Products:

Fumes produced when heated to decomposition may include: carbon monoxide, carbon dioxide

Conditions to Avoid:

Storage >100°F/38°C, exposure to light, loss of dissolved air, loss of polymerization inhibitor, contamination with incompatible materials.

Incompatibility (Materials to Avoid):

Polymerization initiators including peroxides, strong oxidizing agents, copper, copper alloys, carbon steel, iron, rust and strong bases.

Hazardous Polymerization: May occur -- Uncontrolled polymerization may cause rapid evolution of heat and increased pressure that could result in violent rupture of sealed storage vessels or containers.

 SECTION 11: TOXICOLOGICAL INFORMATION

Acute Oral Toxicity

No information available

Acute Dermal Toxicity

No information available

Acute Inhalation Toxicity

No information available

Irritation-skin

No information available

Irritation - Eye

No information available

Since this product contains a very low concentration of active components, the primary toxicological information is derived from the oligomers. Further hazardous properties cannot be excluded. The product should be handled with care when dealing with chemicals.

Sensitization

N/DA

Mutagenicity

N/DA

Sub-chronic Toxicity

N/DA

 SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicological Information**Acute Toxicity to Fish**

N/DA

Acute Toxicity to Invertebrates

N/DA

Acute Toxicity to Algae

N/DA

Bioconcentration

N/DA

Toxicity to Sewage Bacteria

N/DA

Chemical Fate Information**Biodegradability**

N/DA

Chemical Oxygen Demand

N/DA

To the best of our knowledge, the ecotoxicological and chemical fate properties have not been thoroughly investigated.

Do not allow to enter drinking water supplies, wastewater, or soil

 SECTION 13:

Non-contaminated, properly inhibited product is not a RCRA hazardous waste. It is the generators responsibility to determine what is classified as a hazardous waste. Comply with all federal, state, and local regulations.

Dispose of diking materials and absorbent in compliance with State, Local, and Federal regulations.

Residual vapors may

explode on ignition; do not cut, drill, or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate.

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

 SECTION 14: TRANSPORT INFORMATION

DOT (49 CFR 172)

Proper Shipping Name:	Non-Regulated Material
Identification Number:	N/A
Marine Pollutant:	No
Special Provisions:	N/A

Emergency Response Guidebook (ERG) #: N/A**IATA (DGR):**

Proper Shipping Name:	Non-Regulated Material
Class or Division:	N/A
UN or ID Number:	N/A
Packaging Instructions:	

Emergency Response Guidance (ICAO)#:**IMO (IMDG):**

Proper Shipping Name:	Non-Regulated Material
Class or Division:	N/A
UN or ID Number:	N/A
Special Provisions & Stowage/Segregation:	None

Emergency Schedule (EmS)#:**Other Information:** Flash point > 100°C

 SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Clean Air Act: HAP/ODS by the	This product contains the following hazardous air pollutants (HAP), as defined U. S. Clean Air Act: • NONE This product contains no ODS's
-------------------------------	---

Clean Water Act: Priority Pollutant List.	This product contains no chemicals listed under the U. S. Clean Water Act Priority Pollutant
---	--

FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and /or other applications as an indirect food additive.
----------------------------	---

Occupational Safety and Health Act	This product is considered to be a hazardous chemical under the OSHA Hazard Communication Standard. Its hazards are: • Immediate (acute) health hazard • Delayed (chronic) health hazard • Reactive hazard
------------------------------------	---

RCRA	This product is not considered to be a hazardous waste under RCRA (40 CFR 261).
------	---

SARA Title III: Section 302 (TPQ)	This product contains no chemicals regulated under Sec. 302 as extremely hazardous substances that carry a TPQ.
-----------------------------------	---

SARA Title III: Section 302 (RQ)	This product contains no chemicals regulated under Section 304 as extremely hazardous chemical for emergency release notification ("CERCLA" List).
----------------------------------	--

SARA Title III: Section 311-312:	This product is considered hazardous under the OSHA Hazard Communication Standard and is regulated under Section 311-312 (40 CFR 370). Its hazards are: • Immediate (acute) health hazard • Delayed (chronic) health hazard • Reactive hazard
----------------------------------	--

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

SARA Title III: Section 313:	This product contains no chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.
TSCA Section 8(b): Inventory:	This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA premanufacture notification requirements.
TSCA Significant New Use Rule:	None of the chemicals listed have a SNUR under TSCA.

State Regulations

CA Right-to-Know Law:	NONE
California No Significant Risk Rule:	NONE
MA Right-to-Know Law:	NONE
NJ Right-to-Know Law:	NONE
PA Right-to-Know Law:	NONE
FL Right-to-Know	NONE
MN Right-to-Know	NONE

International Regulations

CDSL: Canadian Inventory	Hydroxypropyl methacrylate CAS #27813-02-1 is on the DSL List. WHMIS = D2B Hydroxycyclohexyl phenyl ketone CAS# 947-19-3 is on the DSL list. WHMIS = n/da 2-Hydroxyethyl methacrylate CAS# 868-77-9 is on the DSL List. WHMIS = n/da
--------------------------	--

Labeling according to EC directives – 1999/45/EC

- **HAZARD SYMBOLS: Xi: Irritant**
- **RISK PHRASES: R22: Harmful if swallowed, R36/38: Irritating to eyes and skin R43: May cause sensitization by skin contact.**
- **SAFETY PHRASES: S18: Handle and open container with care, S24/25: avoid contact with skin and eyes, S36/37: Wear suitable protective clothing and gloves, S38: in case of insufficient ventilation, wear suitable respiratory equipment.**

SECTION 16: OTHER INFORMATION

EU Classes and Risk / Safety Phrases for Referenced Ingredients (See Section 2):

Hazard Symbol:

Xi – Irritants

Risk Phrases:

R36/37/38 Irritating to eyes, respiratory system and skin; R36/38 Irritating to eyes and skin; R43 May cause sensitisation by skin contact

Safety Phrases:

S2 Keep out of the reach of children; S3/7 Keep container tightly closed in a cool place; S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice; S28 After contact with skin, wash immediately with plenty of water; S36/37 Wear suitable protective clothing and gloves; S62 If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label

Hazard Symbol:

Xi – Irritants

Risk Phrases:

R36/37/38 Irritating to eyes, respiratory system and skin; R36/38 Irritating to eyes and skin; R43 May cause sensitisation by skin contact

Safety Phrases:

S2 Keep out of the reach of children; S3/7 Keep container tightly closed in a cool place; S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice; S28 After contact with skin, wash immediately with plenty of water; S36/37 Wear suitable protective clothing and gloves; S62 If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.